

**MATERIAL SAFETY DATA SHEET****1.PRODUCT IDENTIFICATION**

TRADE NAME (as labeled): LATICRETE R Super Flexible Mortar Additive 333

CHEMICAL FAMILY:Latex Emulsion Polymer

MANUFACTURER'S NAME: MYK LATICRETE INDIA PVT. LTD.

8-2-703/A, 4th floor Leela Gopal Towers

Road No-12, Banjara Hills, Hyderabad – 500034

Tel: +91 40 30413100

Reviewed & Approved by

Dr.P.Arjunan

Vice President – R&D

II.HAZARDOUS INGREDIENTS

CHEMICAL NAMES	CAS NUMBERS	PERCENT	ACGIH TLV	OSHA PEL	OTHER (SPECIFY)
Ethylene Glycol	107-21-1	2	50 ppm	N/A	N/A
Diethylene Glycol	111-46-6	0.2	N/A	N/A	N//A

W.H.M.I.S Class D.2

*SARA Title 111 section 311 and 312 listing as: - An Immediate Health Hazard

* Subject to SARA Tile 111, Section 313 reporting

A = Not applicable or available**III.PHYSICAL PROPERTIES**

Vapour density (air =1): N/A

Melting point or range, F: N/A

Specific gravity: 1.01

Boiling point or range, F: 200 F

Solubility in water: Dispersal

Evaporation rate (butyl acetate =1): N/A

Vapour pressure,mm Hg at 20 C:N/A

Ph:9 minimum

Appearance and odor: White,liquid, Slight sweet odor

HOW TO DETECT THIS SUBSTANCE (warning properties of substance as a gas, vapor, dust, or mist): N/A

This information is furnished without warranty, representation, inducement or license of any kind; Expect that it is accurate to the best of our knowledge, or obtained from sources believed by us to be Accurate.

LATICRETE Super Flexible Mortar Additive 333

IV. FIRE AND EXPLOSION

Flash Point, F (give method): Not flammable

Auto ignition temperature, F: N/A

Flammable limits in air, volume % : N/A

Lower (LEL)_____ Upper (UEL)

Fire extinguishing materials: N/A

_____ water spray

_____ carbon dioxide

_____ other:

_____ foam

_____ dry chemical

Special fire fighting procedures: N/A

Unusual fire and explosion hazards: Material may splatter if heated above 200 F

V. HEALTH HAZARD INFORMATION

SYMPTOMS OF OVEREXPOSURE for each potential route of exposure.

Inhaled: Symptoms not expected, may cause slight irritation of nose and throat

Contact with skin or eyes: Some irritation

Absorbed through skin: N/A

Swallowed: Single dose toxicity is moderate. Excessive doses may cause central nervous system defects,

Cardiopulmonary defects, and kidney failure

HEALTH EFFECTS OR RISKS FROM EXPOSURE. Explain in lay terms . Attach extra page if more space is needed:

Acute: May provoke asthmatic response in person with asthma who are sensitive to airway irritants.

Chronic: N/A

FIRST AID: EMERGENCY PROCEDURES

Eye Contact: Flush eyes with cold water .If irritation persists, call physician.

Skin Contact: Wash from skin with soap and water. If irritation persists, call physician

Inhaled : No first aid is normally required. Remove to fresh air and seek medical advice if any unusual symptoms develop.

Swallowed: Induce vomiting and call physician..

SUSPECTED CANCER AGENT ?

_____ NO: This product's ingredients are not found in the lists below.

YES: _____ Federal OSHA _____ NTP _____ IARC

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: May provoke asthmatic response in persons with asthma who are sensitive to airway irritation.

LATICRETE R Polymer Fortified Wall Grouts, Dry Set Wall Grout

VI. REACTIVITY DATA

Stability: Stable Unstable

Conditions to avoid: Avoid moisture until used.

Incompatibility (material to avoid): Oxidizing agents.

Hazardous decomposition products (including combustion products): Upon combustion, carbon monoxide, Carbondioxide, nitrogen oxides, ammonia.

Conditions to avoid: Avoid moisture until used.

VII. SPILL, LEAK, AND DISPOSAL PROCEDURES

Spill response procedure (include employee protection measures): Wear appropriate equipment to prevent

Skin and eye contact: also a dust mask approved by NIOSH. Vacuum or scoop the spilled material for Recovery or disposal.

Preparing wastes for disposal (container types, neutralization, etc.): Place in containers for disposal in Landfill.

Note: Dispose of all wastes in accordance with federal, state and local regulations.

VIII. SPECIAL HANDLING INFORMATION

Ventilation and engineering controls: Normal ventilation

Respiratory protection (type): A NIOSH approved dust mask if PEL is exceeded.

Eye protection (type): Chemical goggles or safety glasses

Gloves (specify material): Use impervious gloves, vinyl or rubber.

Other clothing and equipment: Wear appropriate clothing to prevent skin contact. Barrier creams will Assist in protecting the skin from contamination.

Work practices, hygienic practices: Normal good housekeeping practice.

Other handling and storage requirements : Store in a dry area.

Protective measures during maintenance of contaminated equipment: Wear gloves to prevent skin contamination, also wear safety glasses and a NIOSH approved dust mask.

