



MATERIAL SAFETY DATA SHEET

1.PRODUCT IDENTIFICATION

TRADE NAME (as labeled):1776 Liquid Admix, Latex Thinset Mortar Additive 4237, 4230,4325, 3810, 3811,3812,4237 Rapid , 5150 Rapid

CHEMICAL FAMILY:Styrene – butadiene latex

MANUFACTURER'S NAME: MYK LATICRETE INDIA PVT. LTD.

8-2-703/A, 4th floor Leela Gopal Towers

Road No-12, Banjara Hills, Hyderabad – 500034

Tel: +91 40 30413100

Reviewed & Approved by

Dr.P.Arjunan

Vice President – R&D

II.HAZARDOUS INGREDIENTS

CHEMICAL NAMES	CAS NUMBERS	PERCENT	ACGIH TLV OSHA PEL	OTHER (SPECIFY)
None	N/A	N/A	N/A	N/A

W.H.M.I.S. Code D.2

N/A = Not applicable or available

III.PHYSICAL PROPERTIES

Vapour density (air =1): .624

Melting point or range, F: N/A

Specific gravity: 1.000

Boiling point or range, F: 212 F

Solubility in water: Emulsion

Evaporation rate (butyl acetate =1): N/A

Vapour pressure,mm Hg at 20 C: 17.5 mm

p H: 10.0 + .5

Appearance and odor: White, thick liquid, Slight odor

% volaties by volume:80%

HOW TO DETECT THIS SUBSTANCE (warning properties of substance as a gas, vapor, dust, or mist): N/A

This information is furnished without warranty,representation,inducement or license of any kind; except that it is accurate to the best of our knowledge, or obtained from sources believed by us to be accurate.

1766 Liquid Admix, Latex Thinset Mortar Additive 4237, 4230,4325, 3810,3811,3812,4237 Rapid,5150 Rapid.

IV.FIRE AND EXPLOSION

Flash Point, F (give method): Not flammable or combustibile in liquid form

Auto ignition temperature,F: N/A

Flammable limits in air, volume % : N/A

Lower (LEL)_____ Upper (UEL)

Fire extinguishing materials:

_____ water spray
_____ foam

_____ carbon dioxide
_____ dry chemical

_____ other:

Special fire fighting procedures: N/A

Unusual fire and explosion hazards: N/A

V.HEALTH HAZARD INFORMATION

SYMPTOMS OF OVEREXPOSURE for each potential route of exposure.

Inhaled: No adverse effects are anticipated from inhalation.

Contact with skin or eyes: Short exposure not likely to cause significant skin irritation. Eye contact May cause slight,temporary eye irritation.

Absorbed through skin: Skin absorption is unlikely due to physical properties

Swallowed: Single dose oral toxicity is believed to be low.No hazards anticipated from ingestion
Incidental to industrial exposure.

HEALTH EFFECTS OR RISKS FROM EXPOSURE. Ezplain in lay terms . Attach extra page if more space is needed:

Acute: N/A

Chronic: N/A

FIRST AID: EMERGENCY PROCEDURES

Eye Contact: Irrigate immediately with water for at least 5 minutes.

Skin Contact: Wash off in flowing water or shower.

Inhaled : No adverse effects

Swallowed:No adverse effects anticipated by this route of exposure incidental to proper industrial Handling.

SUSPECTED CANCER AGENT ?

_____ NO: This product's ingredients are not found in the lists below.

YES: _____ Federal OSHA _____ NTP _____ IARC

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: N/A

1766 Liquid Admix, Latex Thinset Mortar Additive 4237,4230,4235,3810,3811,3812,4237
Rapid,

VI. REACTIVITY DATA

Stability: Stable Unstable

Conditions to avoid: May coagulated if frozen at 32 F

Incompatibility (materials to avoid): N/A

Hazardous decomposition products (including combustion products): If dried resin is burned, produces

A dense black smoke and noxious gases (Carbon monoxide and hydrocarbons).

Hazardous polymerization: May occur Will not occur

Conditions to avoid: N/A.

VII. SPILL, LEAK, AND DISPOSAL PROCEDURES

Spill response procedures (include employee protection measures): Flush area with water immediately.

Avoid unnecessary exposure and contact.

Preparing wastes for disposal (container types, neutralization , etc.): Soak up with absorbent materials.

Store in pails or drums. Bury in an approved landfill or burn solid wastes in an adequate incinerator. If enters sanitary sewers, flush with large amounts of water.

NOTE: Dispose of all wastes in accordance with federal, state and local regulations.

VIII. SPECIAL HANDLING INFORMATION

Ventilation and engineering controls: Good general ventilation should be sufficient for most conditions

Respiratory protection (type): No respiratory protection should be needed if good ventilation is maintained.

Eye protection (type): Use Chemical goggles or safety glasses

Gloves (specify material): Impervious gloves, vinyl or rubber

Other clothing and equipment: Wear clean, long – sleeved, body – covering clothing..

Work practices, hygienic practices: Maintain good housekeeping standards

Other handling and storage requirements: Should Store at temperatures between 40- 100F and Used within 12 Months.

Protective measures during maintenance of contaminated equipment: Impervious gloves ,vinyl Or rubber, safety glasses, wear clean, long – sleeved, body – covering clothing.