



PRESERVA PLUS



Nano technology fluorocarbon based impregnating sealer and enhancer, designed for protection and improve the appearance of dull looking textured stones surfaces.

Features / Benefits

- Nano technology based impregnator and enhancer
- Deeper penetration in to substrates
- Excellent Hydro phobic & Oleo phobic properties
- Easy to use Highly resistant to water & oil based staining damages
- U Surfaces treated with Preserva Plus are harder and less slippery
- Easy to use and clean
- U V resistant

Substrates

- | | |
|-------------|--------------|
| • Flagstone | • Marble |
| • Granite | • Lime stone |
| | • Slate |

Areas of application

- For interior & exterior applications of tile and stone surfaces

Certifications

ASTM C-97 /
ASTM C97 M- 09

Member of
Indian Green Building Council



APPLICATION:

SURFACE PREPARATION:

- 1) Remove loose particles, cement based materials and dust from the surfaces to be sealed with MYK Laticrete Preserva Plus.
- 2) Clean the surface with clean water and allow the surface to completely dry.
- 3) Ensure tile/stone surface is already checked for the compatibility and effectiveness of Sealer with tile / stone, by sampling on a small un-obtrusive area and obtain clearance from the project manager / home owner.

MIXING AND APPLICATION:

Note: Shake the container well for one minute before opening the container for use.

1) Apply Preserva Plus uniformly over the surface till it is damp, using a clean white cloth / roller or paint brush.

2) Leave the treated surface 4-5 minutes and remove excess product from the surface using clean white cloth. The cleaning should be done, using white cotton cloth by pressing the cloth on the applied surface and buffing the area in circular motion, before the liquid dries on the surface. In case any dried residue is left on the surface, the same can be removed by reapplication of Preserva Plus and cleaning the excess immediately. Multiple applications may be required for some stones. In case of multiple applications, allow 6 to 12 hours gap between the applications.

3) Allow cure time of 72 hours (Air Cure) for sealer to become completely effective.

TECHNICAL DATA

Appearance	Colorless to Yellow Clear liquid
Specific gravity	0.86
PH	8-10

LIMITATIONS:

- Do not use PRESERVA PLUS on any non recommended surface.
- Protect Metal surfaces, wood surfaces with suitable protection covers to avoid contact with the sealer.
- Should not allow PRESERVA PLUS to dry on the stone surfaces.

- May slightly darken or lighten some surfaces. Some of natural stones may change colour when reacting minerals are present within the stone matrix.
- Sealers will not prevent acid etching and surface wear marks on stone or tile surfaces.
- Subsequent cracks in tile & stones would limit the performance of sealers
- Depending on traffic conditions, exposure to environment and various chemicals, the performance of sealer may be hampered and may have to be applied again as part of maintenance.
- The application of impregnating sealer is the final treatment to tile or stone surface. No further treatments like polishing, cleaning or application of other primers or sealers is recommended as they hamper the performance of impregnating sealer.

PACKAGING:

1 litre, 5 litres and 20 litres.

COVERAGE:

25 sq.feet to 400 sq.feet per litre depending upon the porosity of the substrate

CAUTIONS:

- Store in cool place away from heat and fire.
- CONTAINS SOLVENT. DO NOT SMOKE IN THE JOB SITE AREA.
- Avoid contact with skin and eyes.
- Do not inhale and use it in open ventilated areas.
- Do not swallow and wear gloves during application.
- DO NOT add any liquids like water or solvents or other chemical liquids. Sealers are ready to use products and should be used directly from company supplied containers.

STORAGE:

After usage, close the container well sealed to avoid contamination and solvent loss. Store in original container only. Store and use between temperature 4° C and 40° C

WARRANTY:

MYK LATICRETE India Pvt Ltd warrants to the original customer that MYK Laticrete Preserva Plus is free from manufacturing defect and will not deteriorate or disintegrate under normal usage for a period of 1 year from the date of manufacturing subject to the terms and conditions stated in MYK Laticrete product warranty

MAINTENANCE:

NOTE: All impregnating sealers are maintenance products and hence surfaces applied with sealers need careful maintenance.

Maintenance of the sealed surface should not be done with general cleaner chemicals. Plain soft water is recommended to clean the surface. For periodic cleaning we recommend to use our MYK LATICRETE CLENZA AQ, neutral water based cleaner. Acidic cleaners are STRICTLY NOT recommended. Please refer the Maintenance manual for more details.

TECHNICAL SUPPORT:

Information is available by contacting
MYK LATICRETE Technical service
Telephone: +91-40-68173100
Email: technicalservices@myklaticrete.com

MYK LATICRETE INDIA PVT LTD

8-2-703/A, Fourth Floor, Leela Gopal Towers,
Road No.12, Banjara hills, Hyderabad – 500 034.
Telephone: +91-40-68173100
Email: contact@myklaticrete.com

AVAILABILITY:

MYK LATICRETE materials -
For distributor information
Telephone: +91-40-68173100
Email: contact@myklaticrete.com