

MATERIAL SAFETY DATA SHEET

Reviewed & Approved by, Dr. P. Arjunan, Vice President – R&D

1. IDENTIFICATION OF THE PRODUCT AND NAME OF THE COMPANY/UNDERTAKING

TRADE NAME : MYK LATICRETE SP-100™ Part A Hardener Component

MANUFACTURER'S NAME : MYK LATICRETE INDIA PVT. LTD

8-2-703/A, 4th floor, Leela Gopal Towers

Road No-12, Banjara Hills, Hyderabad – 500034 Tel: +91-40-6817 3100

Recommended use of the chemical and restrictions on use

Recommended use : Epoxy Grout for Tile/Stone joints

Restrictions on use : NA

2. HAZARDOUS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, 4, H302 Acute toxicity, 4, H312 Skin corrosion, 1B, H314 Skin sensitisation, 1, H317

Chronic aquatic toxicity, 3, H4122.2

For the full text of the H-Statements mentioned in this Section, see Section 16.

Classification (67/548/EEC, 1999/45/EC)

Corrosive, C, R34 Sensitizing, Xi, R43

Dangerous for the environment, R52/53

Harmful, Xn, R21/22

For the full text of the R-phrases mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram

Signal word

Danger

Hazard statement(s)

H302 + H312 Harmful if swallowed or in contact with skin

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statement(s)

P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing vapor/ spray.

P270 Do not eat, drink or smoke when using this product

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all

contaminated clothing. Rinse skin with water/ shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do.

Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/ physician.
P337 + P313 If eye irritation persists: Get medical advice/attention.

P403 + P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container to an approved waste

disposal plant in accordance with local, regional, national

and international regulations.

Supplemental Hazard Statement(s)

P264 Wash contaminated skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P333+P313 If skin irritation or rash occurs: Get medical advice/

attention.

P337+P313 If eye irritation persists: Get medical advice/ attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

2.3 Other hazards

No further data available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Ingredients

Chemical Name	CAS-No.	Concentration	Classification according to
		(%)	Regulation (EC) No. 1272/2008
			[CLP]
Fatty acids, tall-oil,	1226892-	60-100%	Skin Corr. 1C, H314;
reaction products with	44-9		Aquatic Acute 1, H400;
triethylenetetramine			Aquatic Chronic 1, H410;
			Skin Sens. 1, H317
Triethylenetetramine	112-24-3	< 1 %	Acute Tox. 4; H302
			Acute Tox. 4; H312
			Skin Corr. 1B; H314
			Skin Sens. 1; H317
			Aquatic Chronic 3; H412

4. FIRST AID MEASURES

Emergency first aid procedures by route of exposure:

General advice: Consult a physician. Show this safety data sheet to the doctor in attendance. If inhaled: If breathed in, move person into fresh air. If not breathing, give artificial respiration.

Consult a physician.

If swallowed: Do not induce vomiting. If the material is swallowed, get medical attention or advice.

In case of skin contact: If irritation is experienced, flush with water. If irritation persists, get medical attention.

In case of eye contact: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing Media:

Suitable extinguishing media Foam. Dry powder. Carbon dioxide. Water spray.

Sand.

Unsuitable extinguishing media Do NOT use High Volume water jet.

5.2 Special hazards arising from the substance or mixture:

Specific hazards during firefighting / Specific hazards

arising from the chemical

Combustion products

Do not allow run-off from fire fighting to enter

drains or water courses.

Carbon oxides

nitrogen oxides (NOx)

5.3 Advice for firefighters

Protective equipment Mouth respiratory protective device.

> Wear self-contained respiratory protective device Do not enter fire area without proper protective

equipment, including respiratory protection

5.4 Specific extinguishing methods:

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Remove undamaged containers from fire area if it is safe to do so.

Avoid breathing fire gases or vapours.

Evacuate area.

Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

Cool containers exposed to flames with water until well after the fire is out.

Avoid discharge to the aquatic environment.

Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

5.5 Fire Fighting Equipment/Instructions:

In the event of fire, Use personal protective equipment, protective clothing and equipment suitable for the surrounding fire, including helmet, facemask, and wear self-contained breathing apparatus.

5.6 NFPA Rating: Health:3 Fire: 1 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

5.7 Further information:

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment, and emergency procedures:

No action shall be taken without appropriate training or involving any personal risk.

Keep unnecessary and unprotected personnel away from the spillage.

Wear protective clothing as described in Section 8 of this safety data sheet.

Follow precautions for safe handling described in this safety data sheet.

Wash thoroughly after dealing with a spillage.

Ensure procedures and training for emergency decontamination and disposal are in place.

Do not touch or walk into spilled material without PPEs.

Avoid contact with skin and eyes.

6.2 Environmental precautions:

Avoid discharge into drains or watercourses or onto the ground.

Avoid discharge to the aquatic environment.

Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

6.3 Methods and materials for containment:

Wear protective clothing as described in Section 8 of this safety data sheet.

Clear up spills immediately and dispose of waste safely.

Approach the spillage from upwind.

Absorb with liquid-binding material (sand, diatomite, universal binders, sawdust).

Clean the affected area carefully;

6.4 Methods and materials for cleaning up:

If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container.

If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows.

The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water.

Wash thoroughly after dealing with a spillage.

6.5 Further Information:

Dangerous for the environment. Do not empty into drains. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling Precautions for safe handling

: Comply with the legal requirements. Keep receptacles tightly sealed. Remove contaminated clothing immediately. Clean contaminated clothing. Do not discharge the waste into the drain. Do not use compressed air for pumping over. Use spark-/explosion proof appliances and lighting system. Observe normal hygiene standards. Keep container tightly closed. Work under local exhaust/ventilation.

Hygiene measures

: Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep container tightly closed. Keep only in the original container in a cool, well ventilated place away from incompatible materials.

Conditions for safe storage, including any incompatibilities

: Miscellaneous hazardous material storage. Store in accordance with local regulations.

Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and dried. Store leaked we

drink. Store locked up.

Keep container tightly closed and sealed until ready for

use.

Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store

in unlabeled containers.

Use appropriate containment to avoid environmental

contamination.

See Section 10 for incompatible materials before handling

or use.

Local/Total ventilation
Special rules on packaging

: Use with local exhaust ventilation.

: SPECIAL REQUIREMENTS: closing. dry. clean. correctly

labelled. meet the legal requirements. Secure fragile

packaging in solid containers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

8.2 Exposure controls

There is no exposure data pertaining to the Product.

8.3 Exposure Controls

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Personal protective equipment Materials for protective clothing

: Safety glasses. Gloves. Protective clothing.

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before

handling this product.

Eye/face protection

: Tight Sealed Goggles and Face shield. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection Respiratory protection

: Protective clothing.

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapor (Type AX) and particulate

filter

Other information

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product

8.4 Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Viscous Liquid Color : Clear, Brownish

Odor : Amine

Odor Threshold : No data available

pH : 8 to 9

Melting point/freezing point : Undetermined Initial boiling point and boiling range : No data available Flash point : No data available **Evaporation rate** : No data available : No data available Flammability (solid, gas) Upper explosion limit : No data available Lower explosion limit : No data available Vapor pressure : No data available

Specific Gravity (20 °C) : 0.960
Viscosity : 700 cps
Water solubility : Insoluble

Partition coefficient: n-octanol/water : No data available
Autoignition temperature : No data available
Explosive properties : Not explosive

Oxidizing properties : The mixture is not classified as oxidizing.

10. STABILITY AND REACTIVITY

Reactivity : Stable under normal conditions of use. Reacts with :

Incompatible materials

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous

reactions will not occur

Conditions to avoid : High temperature. high humidity. Ignition sources.

Incompatible materials.

Incompatible materials : Keep away from oxidizing agents and strongly alkaline

and strongly acidic materials.

Hazardous decomposition : Thermal combustion may release carbon monoxide and

Products dioxide. Fume.

11. TOXICOLOGICAL INFORMATION

There is no data for this product. The information included in this section describes the potential hazards of the individual ingredients.

Information on likely routes of exposure

Product Information

Inhalation May cause irritation of respiratory tract.

Eye Contact Irritating to eyes. May cause redness, itching, and pain.

Skin Contact May cause redness and irritation.

Ingestion Ingestion may cause irritation to mucous membranes. Ingestion

may cause gastrointestinal irritation, nausea, vomiting and

diarrhea.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No further relevant information available

12.2 Persistence and degradability

No further relevant information available

12.3 Bioaccumulative potential

No further relevant information available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available Remarks: Toxic for Fish 12.6 Other adverse effects

Additional ecological information No data available

13. DISPOSAL INFORMATION

Dispose of waste and residues in accordance with local authority requirements.

14. TRANSPORT INFORMATION

14.1 International Regulation

UN proper shipping name

ADR 2735 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylene

bis(methylamine), ISOPHORONEDIAMINE), ENVIRONMENTALLY

HAZARDOUS SUBSTANCE

IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, AMINES,

LIQUID, CORROSIVE, N.O.S. (m-phenylene bis(methylamine)

,ISOPHORONEDIAMINE), MARINE POLLUTANT

IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, AMINES,

LIQUID, CORROSIVE, N.O.S. (m-phenylene bis(methylamine)

,ISOPHORONEDIAMINE), MARINE POLLUTANT

Packing group : Miscellaneous dangerous substances and articles

Labels : 8

14.1 Transport hazard class(es)

ADR/RID: 8 IMDG: 8 IATA: 8

14.2 Packaging group

ADR/RID: II IMDG: II IATA: II

14.3 Environmental hazards

ADR/RID Symbol: Fish and Tree IMDG: Marine pollutant: Yes IATA Symbol: Fish and Tree

14.4 Special precautions for user

No data available

15. REGULATORY INFORMATION

15.1 Safety, health, and environmental regulations/legislation specific for the substance or mixture

Harmful Chemicals List: Listed

16. OTHER INFOMATION

Full text of H-Statements referred to under sections 2 and 3.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Full text of R-phrases referred to under sections 2 and 3

R21/22 Harmful in contact with skin and if swallowed.

R34 Causes burns.

R43 May cause sensitisation by skin contact.

R52 Harmful to aquatic organisms.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in

the aquatic environment.

R53 May cause long-term adverse effects in the aquatic environment.

Explanations for possible abbreviations mentioned in section 2

PBT : Persistent, bioaccumulative and toxic. vPvB : vPvB: Very persistent and very bioaccumulative.

OEL: Occupational exposure limit.

Further information

This information is furnished without warranty, representation, inducement or license of any kind; except that it is accurate to the best of our knowledge, or obtained from sources believed by us to be accurate